



Premium AT Fluid

PREMIUM AT FLUID
ZWA5301A / A5302A / A5303A

SUITABLE FOR USE CHART

	OEM / ATF	APPLICATION	VIS	Suitable
Acura	Acura	ATF-Z1	H	S
AISIN	AISIN	AW-2	UL	S
	AISIN	JWS 3309 ATF, ATF-OT4	H	S
	AISIN	JWS 3324 ATF, ATF-OWS	L	S
Allison	Allison	C2	H	S
	Allison	C3	H	S
	Allison	TES-389	H	S
	Allison	C4	H	S
ATF	ATF	134	L	S
	ATF	ATF RED 1, RED 1K	L	
	ATF	3353	L	S
	ATF	3100 PL085	H	S
	ATF	3403-M115	H	S
	ATF	D971	UL	S
	ATF	ETL-7045 E	H	S
	ATF	K17	H	S
	ATF	L12108	L	S
	ATF	LA 2634	H	S
	ATF	M-1375.4	L	S
	ATF	M-1375.6	L	S
	ATF	N402	H	S
	ATF	SP-III	H	S
Bentley	Bentley	P/N PY112995PA	L	S
BMW/Mini	BMW	BMW 3.0 and 3+	H	S
	BMW	JWS 3309(T-IV)	H	S
	BMW	ZF 5HP 18FL,5HP,5HP24, 5HPP30	H	S
	BMW	ZF life guard fluid 6 and 8	L	
	BMW	83 22 9 407 765	H	S
	BMW	ATF 3+	L	S
	BMW	ATF 7	UL	S
	BMW	ATF4	H	S
	BMW	ATF6	L	S
	BMW	ETL-7045	H	S
	BMW	ETL-7045 E	H	S
	BMW	ETL-8072B	H	S
	BMW	LA 2634	H	S
	BMW	LT 71141	H	S
	BMW	M-L12108	L	S
	BMW	P/N 81 22 9 400 272/275	H	S
	BMW	P/N 81 22 9 407 858/859	H	S
	BMW	P/N 83 22 0 024 249	H	S
	BMW	P/N 83 22 0 024 359	H	S
	BMW	P/N 83 22 0 026 922	H	S
	BMW	P/N 83 22 0 142 516	L	S
	BMW	P/N 83 22 0 397 114	L	S
	BMW	P/N 83 22 0 402 413 - JWS 3309	H	S
	BMW	P/N 83 22 0 403 248/249	H	S

KEY: S = suitable for use, N = not suitable for use. As ATF specifications have diverse viscometric requirements, not all may be met with multi-vehicle products.

REV: 8.19.2025



Premium AT Fluid

PREMIUM AT FLUID
ZWA5301A / A5302A / A5303A

SUITABLE FOR USE CHART

	OEM / ATF	APPLICATION	VIS	Suitable
BMW/Mini	BMW	P/N 83 22 2 152 426	L	S
	BMW	P/N 83 22 2 163 514	L	S
	BMW	P/N 83 22 2 220 438/440	H	S
	BMW	P/N 83 22 2 220 442	H	S
	BMW	P/N 83 22 2 289 720	L	S
	BMW	P/N 83 22 2 305 396	L	S
	BMW	P/N 83 22 2 305 397	L	S
	BMW	P/N 83 22 2 355 599	L	S
	BMW	P/N 83 22 2 355 601	L	S
	BMW	P/N 83 22 2 413 477	UL	S
	BMW	P/N 83 22 7 542 290	H	S
	BMW	P/N 83 22 9 407 765	H	S
	BMW	P/N 83 22 9 407 807	H	S
Bosch	Bosch	Bosch TE-ML 09	H	S
Citroen	Citroen	Z 000169756	H	S
Daewoo	Daewoo	LT 71141	L	S
Daihatsu	DAIHATSU	AMMIX ATF D-11	H	S
Daihatsu	DAIHATSU	DIII-SP	H	S
FCA Fiat/Chrysler/ Dodge/Jeep/ Ram	Fiat/Chry/dod/jeep	8 & 9 Speed ATF, P/N 68218925AA/AB	L	S
	FCA	ASRC	H	S
	FCA	ATF+/+2/+3and +4	H	S
	FCA	Mopar/Dodge AS 68 RC	L	S
	FCA	AW-1, P/N 68092912AA	L	S
	FCA	Dex-VI, P/N 68043742AA	L	S
	FCA	Fiat 9.55550-AV1	H	S
	FCA	Fiat 9.55550-AV2	L	S
	FCA	Fiat 9.55550-AV4	H	S
	FCA	Fiat 9.55550-AV5	L	S
	FCA	Fiat 9.55550-AV6	L	S
	FCA	MB 236.10/12, P/N 05127382AA	H	S
FCA Fiat/Chrysler/ Dodge/Jeep/ Ram	FCA	P/N 68043742AA	L	S
	FCA	P/N 05127382AA	L	S
	FCA	P/N 68157995AA/AB	L	S
	FCA	P/N 68333587AA	H	S
	FCA	SP-4, P/N 68171866AA	L	S
	FCA	SP-III	H	S
	FCA	SP-IV, P/N 68171866AA	L	S
	FCA	SP-IV, P/N 68171869AA	L	S
FIAT	FCA	Type 7176E	H	S
	FCA	Type 9602	H	S
FIAT	FIAT	T-IV type, JWS 3309	H	S

KEY: S = suitable for use, N = not suitable for use. As ATF specifications have diverse viscometric requirements, not all may be met with multi-vehicle products.

REV: 8.19.2025



Premium AT Fluid

PREMIUM AT FLUID
ZWA5301A / A5302A / A5303A

SUITABLE FOR USE CHART

	OEM / ATF	APPLICATION	VIS	Suitable
Ford/Lincoln	Ford	ST-9-QMMF5	L	S
	Ford	MERCON SP (XTG-QSP & -DSP)	L	S
	Ford	FNR5	H	S
	Ford	ESP-M2C138-CJ	H	S
	Ford	ESP-M2C166-H	H	S
	Ford	P/N XT-10-QLV [LV]	L	S
	Ford	P/N XT-12-ULV [ULV]	UL	S
	Ford	P/N XT-2-QDX [M]	H	S
	Ford	P/N XT-2-QSM [Syn]	H	S
	Ford	P/N XT-5-QM [V]	H	S
	Ford	P/N XT-5-QSM [V Syn]	H	S
	Ford	P/N XT-6-QSP [SP]	L	S
	Ford	P/N XT-8-QAW [Premium]	H	S
	Ford	P/N XT-9-QMM5 [FNR5]	H	S
Ford	Spec WSS-M2C922-A1,924A(XT-8-QAW) JWS3309	H	S	
Fuso	Fuso	ATF-II	H	S
	Fuso	ATF-SPIII	L	S
	Fuso	ATF -A4	L	S
GM Chevrolet/ Cadillac/Buick/ GMC/Saturn	GM	ATF Z1, Saturn P/N 22717466	H	S
	GM	TASA	L	S
	GM	OPEL/SATURN 88863400	L	S
	GM	OPEL/SATURN AW-1	UL	S
	GM	OPEL/SATURN 88863401	L	S
	GM	Dex II	H	S
	GM	AW-1, P/N 19256039	L	S
	GM	Dex [GM 6032M]	H	S
	GM	Dex HP [GMW 16974]	L	S
	GM	Dex ULV, P/N 19352619	UL	S
	GM	Dex-B [GM 6032M]	H	S
	GM	Dex-IIC [6137M]	H	S
	GM	Dex-IID [GM 6137M]	H	S
	GM	Dex-IIE [GM 6137M]	H	S
	GM	Dex-IIIF [GM 6297M]	H	S
	GM	Dex-IIIG [GM 6417M]	H	S
	GM	Dex-IIIH [GM N10055]	H	S
	GM	Dex-VI [GMW 16444]	L	S
GM	P/N 19 40 700	H	S	

KEY: S = suitable for use, N = not suitable for use. As ATF specifications have diverse viscometric requirements, not all may be met with multi-vehicle products.

REV: 8.19.2025



Premium AT Fluid

PREMIUM AT FLUID
ZWA5301A / A5302A / A5303A

SUITABLE FOR USE CHART

	OEM / ATF	APPLICATION	VIS	Suitable
GM Chevrolet/ Cadillac/Buick/ GMC/Saturn	GM	P/N 19 40 767	H	S
	GM	P/N 1940771; 19 40 771	H	S
	GM	P/N 1940773; 19 40 773	L	S
	GM	P/N 21005966	H	S
	GM	P/N 88900925	H	S
	GM	P/N 9985010/9985835	H	S
	GM	GM aAutotrackII	L	S
	GM	P/N 93160393	L	S
	GM	P/N 9986195 (ASIN AW, JW 3309)	H	S
	GM	Saturn T-IV Fluid, Saturn P/N 22689186	H	S
	GM	Type A Suffix A	H	S
	GM	WS, P/N 88863400 / 88863401	L	S
Hino	HINO	Blue Ribbon ATF	H	S
Honda/Acura	Honda/Acura	Ultra HEVF-Type 1	UL	S
	Honda/Acura	ATF DW-1 P/N 08200-9008	L	S
	Honda/Acura	ATF Type 3.0 P/N 08200-9016-A	L	S
	Honda/Acura	ATF Type 3.1 P/N 08200-9017	L	S
	Honda/Acura	ATF Z1, P/N 08200-9001	H	S
	Honda/Acura	ATF Z1, P/N 08200-9001A	H	S
Hyundai/Kia	Hyundai/Kia	ATF RED-1K	H	S
	Hyundai/Kia	ATF SP-IV	L	S
	Hyundai/Kia	Genuine ATF	H	S
	Hyundai/Kia	JWS 3314	H	S
	Hyundai/Kia	P/N 00232-19023	H	S
	Hyundai/Kia	P/N 040000C90SG	L	S
	Hyundai/Kia	P/N 04500-00140	H	S
	Hyundai/Kia	P/N UM040 CH20 Red-1	H	S
	Hyundai/Kia	SP	H	S
	Hyundai/Kia	SP4-M1	L	S
	Hyundai/Kia	SPH-IV and SPH-IV M,	L	S
	Hyundai/Kia	SP-II	H	S
	Hyundai/Kia	SP-III	H	S
	Hyundai/Kia	SP-IV	L	S
	Hyundai/Kia	SP-IV-RR	L	S
Hyundai/Kia	WS, spec NWS-9638	L	S	
Idemitsu	Idemitsu	K173100PL085	UL	S
Isuzu	Isuzu	Besco ATF -SP	H	S
	Isuzu	ATF II	H	S
	Isuzu	ATF III	H	S
	Isuzu	ATF WSI	L	S
	Isuzu	Genuine ATF	H	S
	Isuzu	P/N 08200-9001	H	S
	Isuzu	SCS Fluid	L	S

KEY: S = suitable for use, N = not suitable for use. As ATF specifications have diverse viscometric requirements, not all may be met with multi-vehicle products.

REV: 8.19.2025



Premium AT Fluid

PREMIUM AT FLUID
ZWA5301A / A5302A / A5303A

SUITABLE FOR USE CHART

	OEM / ATF	APPLICATION	VIS	Suitable
Jaguar	Jaguar	02JDE 26444	L	S
	Jaguar	Fluid 8432	L	S
	Jaguar	JLM 20238	H	S
	Jaguar	JLM 20292	H	S
	Jaguar	JLM 21044	H	S
	Jaguar	K17, Jatco 3100 PL085	H	S
	Jaguar	ATF 3403 JLM20238	L	S
	Jaguar	LT 71141, ZF5HP24	H	S
	Jaguar	WSS-M2C922-A1	H	S
Japanese automotive standard	Jaso	M315-2013A	H	S
	Jaso	M315-2013 1A-LV	L	S
	Jaso	M315-2013 2A	H	S
Land Rover	Land Rover	ATF N402	H	S
	Land Rover	AW-1 P/N LR0022460: LV	L	S
	Land Rover	JWS3309US	H	S
	Land Rover	P/N TYK500050	L	S
	Land Rover	STC4863	H	S
	Land Rover	LR023288/023289	L	S
MAN	MAN	339A	H	S
	MAN	339D	H	S
	MAN	339F	H	S
Maserati	Maserati	Oil No. 231603	L	S
Mazda	Mazda	ATF A7	UL	S
	Mazda	ATF FZ	L	S
	Mazda	ATF M-5 P/N 0000-23-ATF -M5	H	S
	Mazda	ATF N-1	H	S
	Mazda	ATF S-1	H	S
	Mazda	F-1	H	S
	Mazda	JWS3317	H	S
	Mazda	M3	H	S
	Mazda	ATF D-II	H	S
	Mazda	ATF M-III	H	S
	Mazda	ATF M-V	L	S
	Mazda	Type T-IV, JWS 3309 ATF	H	S
Mercedes	Mercedes	A 0019892203	H	S
	Mercedes	ATF 3403-M115	H	S
	Mercedes	236.1 [DTFR 13C100]	H	S
	Mercedes	236.1	H	S
	Mercedes	236.11 [DTFR 13C110]	H	S
	Mercedes	236.12	L	S
	Mercedes	236.14	L	S
	Mercedes	236.15	UL	S
	Mercedes	236.16	UL	S
	Mercedes	236.17	UL	S
	Mercedes	236.2 [DTFR 13C120]	H	S
	Mercedes	236.41	L	S
	Mercedes	236.5	H	S

KEY: S = suitable for use, N = not suitable for use. As ATF specifications have diverse viscometric requirements, not all may be met with multi-vehicle products.

REV: 8.19.2025



Premium AT Fluid

PREMIUM AT FLUID
ZWA5301A / A5302A / A5303A

SUITABLE FOR USE CHART

	OEM / ATF	APPLICATION	VIS	Suitable
Mitsubishi	Mitsubishi	ATF-J2	H	S
	Mitsubishi	ATF-J3	L	S
	Mitsubishi	Dia Queen ATF-MA1, P/N MZ320775	L	S
	Mitsubishi	Dia Queen ATF-PA, P/N 4030401	L	S
	Mitsubishi	Dia Queen AW	H	S
	Mitsubishi	Dia Queen SK	H	S
	Mitsubishi	DII/DIII	H	S
	Mitsubishi	SP, P/N MS991156	H	S
	Mitsubishi	SP-II	H	S
	Mitsubishi	SP-III	H	S
Mitsubishi	SP-IV	L	S	
Nissan/Infinti	Nissan	Fluid A	H	S
	Nissan	Fluid C	L	S
	Nissan	Matic D	H	S
	Nissan	Matic J, P/N 999MP-MTJ00P	H	S
	Nissan	Matic K	H	S
	Nissan	Matic P, P/N 999MP-MTP10P	UL	S
	Nissan	Matic R, P/N 999MP-MTR00P	L	S
	Nissan	Matic S, P/N 999MP-MTS00P	L	S
	Nissan	Matic W	L	S
Nissan	N402	H	S	
Peugeot	Peugeot/Citreon	P/N Z 000169756	H	S
	Peugeot	ZF 4 HP20	S	S
	Peugeot	PSA 16 350 560 80	UL	S
Porsche	Porsche	JWS 3309, P/N 000 043 205 28	H	S
	Porsche	LT 71141	H	S
	Porsche	ATF 3403-M115	L	S
	Porsche	P/N 000 043 204 41	H	S
	Porsche	P/N 000 043 204 63	H	S
	Porsche	P/N 000 043 304 00/01	L	S
	Porsche	P/N 000 043 305 42	H	S
	Porsche	P/N 000 043 305 43	L	S
	Porsche	P/N 000 043 305 54	L	S
	Porsche	P/N 000 043 306 24	L	S
	Porsche	P/N 958 300 540 00	L	S
	Porsche	P/N 958 300 901 00	H	S
Porsche	P/N 999 917 547 00 (A2) or P/N 000 043 205 09	H	S	
PSA	PSA	AL4 / 4HP20, P/N 9730AE	H	S
	PSA	B71 2340	H	S
Renault	Renault	DP-0/AL4	H	S
	Renault	Matic D2	H	S
	Renault	SATF-D	H	S
Rolls Royce	Rolls Royce	Oil No. PL 31493PA	H	S
Saab	Saab	ATF HP	H	S
	Saab	JWS 3309	H	S
	Saab	P/N 93 160 393	H	S
	Saab	P/N 93 165 147	L	S

KEY: S = suitable for use, N = not suitable for use. As ATF specifications have diverse viscometric requirements, not all may be met with multi-vehicle products.

REV: 8.19.2025



Premium AT Fluid

PREMIUM AT FLUID
ZWA5301A / A5302A / A5303A

SUITABLE FOR USE CHART

	OEM / ATF	APPLICATION	VIS	Suitable
Scion	Scion	All Vehicles	L	S
Shell	Shell	134	L	S
	Shell	3353	H	S
	Shell	M-13475.4	L	S
Ssangyong	Ssangyong	DSIH 5M-52	H	S
	Ssangyong	DSIH 5M-66	H	S
Subaru	Subaru	ATF HP, P/N K0140Y0700, P/N SOA635040	H	S
	Subaru	Dexron-II	H	S
	Subaru	ATF HP	L	S
	Subaru	ATF 5AT	L	S
	Subaru	ATF-WS	L	S
Suzuki	Suzuki	JWS 3309	H	S
	Suzuki	ATF 2326	H	S
	Suzuki	ATF 2384K	H	S
	Suzuki	ATF 3314	H	S
	Suzuki	ATF 3317	H	S
	Suzuki	ATF 5D06	H	S
	Suzuki	Matic D	H	S
	Suzuki	Matic J	H	S
	Suzuki	ATF 5AT	L	S
Suzuki	Matic S	L	S	
Texaco	Texaco	N402	L	S
	Texaco	8072B	H	S
	Texaco	7045-E	H	S
Toyota/Lexus	Toyota	ATF FZ	L	S
	Toyota	JWS 3309, Type T-IV, P/N 08886-81015	H	S
	Toyota	JWS 3324, ATF WS (or NWS9638)	L	S
	Toyota	Type D-II and D-III	H	S
	Toyota	Type T and T-IV	H	S
	Toyota	Type T-II	H	S
	Toyota	ATF WS	H	S
	Toyota	Type T-III	H	S
Volvo	Volvo	P/N 1161521	H	S
	Volvo	97325	H	S
	Volvo	CE 97341 and CE 97340	L	S
	Volvo	97335	L	S
	Volvo	P/N 1161621	H	S
	Volvo	P/N 1161640; P/N 1161540	H	S
	Volvo	P/N 31 256 774, 31 256 775	L	S
	Volvo	P/N 31 492 172, 31 492 173	UL	S
VW/Audi	VW/Audi	G 052 162 A1, A2 [AG4]	H	S
	VW/Audi	G 052 533	L	S
	VW/Audi	G 052 025 A2	L	S
	VW/Audi	G 052 990 A2	H	S
	VW/Audi	G 053 025 A2	L	S
	VW/Audi	G 053 001 A2	UL	S
	VW/Audi	G 055 005 A2	L	S

KEY: S = suitable for use, N = not suitable for use. As ATF specifications have diverse viscometric requirements, not all may be met with multi-vehicle products.

REV: 8.19.2025



Premium AT Fluid

PREMIUM AT FLUID
ZWA5301A / A5302A / A5303A

SUITABLE FOR USE CHART

	OEM / ATF	APPLICATION	VIS	Suitable
VW/Audi	VW/Audi	G 055 025 A2	H	S
	VW/Audi	G 055 162 A2, A6	L	S
	VW/Audi	G 055 540 A2	L	S
	VW/Audi	G 060 162 A2	L	S
	VW/Audi	G 060 540 A2	UL	S
	VW/Audi	G US 000 162	H	S
	VW/Audi	LT 71141	H	S
ZF	ZF	LifeguardFluid 5 (ZF No. S671 090 170)	H	S
	ZF	LifeguardFluid 6 (ZF No. S671 090 255)	L	S
	ZF	LifeguardFluid 8 (ZF No. S671 090 312)	L	S
	ZF	LifeguardFluid 9 (ZF No. AA01.500.001)	L	S
	ZF	TE-ML 05L	L	S
	ZF	TE-ML 11A	H	S
	ZF	TE-ML 21L	L	S
	ZF	TE-ML 09 X	H	S
	ZF	ZF TE-ML 09	H	S
	ZF	TE-ML 11B	H	S

NOT SUITABLE FOR USE

Allison	Allison	295*	H	N
	Allison	389	H	N
GM Chevrolet/Cadillac/Buick/GMC/Saturn	GM	P/N 12378515*	H	N
	Hyundai/Kia	Hyundai/Kia SP-III (CVT Model)	H	N
Mercedes	Mercedes	236.6*	H	N
	Mercedes	236.7 [DTR13C140]*	H	N
	Mercedes	236.8 [DTR13C150]*	H	N
	Mercedes	236.9 [DTR13C170]*	H	N
	Mercedes	236.91 [DTR13C180]*	H	N
	Mercedes	722.9 (ATF 7134 FE)	H	N
	Volvo	Volvo CE	97325*	H
Volvo	Volvo CE	97335*	H	N
	Volvo CE	97337*	H	N
	Volvo CE	97340, AT100	H	N
	Volvo CE	97341, AT101	H	N
ZF	ZF	TE-ML 05L	H	N
	ZF	TE-ML 21L	H	N
eMobility Applications				
Ford	Escape Hybrid with eCVT		E	N
Honda	e:HEV		E	N
Honda	IMMD		E	N
Jatco	JR712E		E	N
Jatco	CVT 8 Hybrid		E	N
Mazda	Skyactive Hybrid		E	N
Nissan	ePower		E	N
Nissan	Altima Hybrid		E	N
Tesla	Model 3		E	N
Toyota	THSII/Toyota Prius		E	N
Toyota	THS 5th Gen./Noah, Voxy, etc.		E	N

KEY: S = suitable for use, N = not suitable for use. As ATF specifications have diverse viscometric requirements, not all may be met with multi-vehicle products.

REV: 8.19.2025